









GUARANTEE

COMMERCIAL



- allure Locking brings the versatility and natural look of Extra Wide and Rusty collections, state-of-the-art innovative LVT resilient flooring products.
- allure Locking offers the benefits of simple, no glue installation with no requirement of underlay or heavy tools, making it cheaper, quicker and cleaner to install.
- Completely waterproof, allure Locking is also warm and quiet underfoot. The product is durable and hygienic, making it suitable for retail, office, hospitality, leisure and residential purposes.
- The first Locking system to be launched in the resilient flooring industry, allure Locking has a proven track record of successfull installations and durability.
- allure Locking is produced with 100% pure virgin PVC, with all quality and health aspects under strict control.
- Completely recyclable because there are no glue residues or discontaminants, allure Locking can also be dismantled and reinstalled, making it the perfect environmentally sustainable product.







Cezanne - 969107







Southern Hickory White - 100211



Van Gogh - 969101







Southern Hickory Red - 100217



Golden Oak MOcha - 96714







Smoked Oak Grey - 966104



Matisse - 969106







Rustic Nutmeg - 971102



Rustic Forest - 971105











Technical Specifications

allure LOCKING	Extra Wide
Thickness (mm)	5.00
Wear Layer (mm)	0.55
Utilization Class	
Coating	PU with Ceramic Bead (CB)
Embossing	True-Wood Structure
Bevelled	yes
Fiberglass	yes
Plank Size	220 x 1210 mm
Sqm per Plank / Pack	0.266 m ² / 1.86 m ²
Pallet Packing	66.9 m2 / 36 packs
Planks per Pack	7 planks
Net Wt/Gross Wt per Pallet	680 kg / 730 kg
Impact Sound Insulation ISO 717-2	5 dB
Chemical Resistance EN 423	High Resistance
Residual Indentation EN 433	≤ 0,08 mm
Dimensional Stability EN 434	≤ 0,08%
Color Fastness to Light EN 20105-B02	≥ 6
Slip Resistance DIN 51130	R10
Watertightness EN13553	No Penetration
Wear Resistance EN 660-2	Group T
Antimicrobial Activity ASTM G 21-96	Class 0
Fire Rating EN ISO 9239-1	Bfl -S1
Warranty for Domestic use	25 Years
Warranty for Commerical use	10 Years

#