

SPECIFICATIONS

CONSTRUCTION	STANDARDS	Diamond Standart Fresh	Acoustic Neo
DESCRIPTION			
Construction		compact heterogeneous	heterogeneous
Total thickness	EN ISO 24346	2,0 mm	3,2 mm
Wear layer thickness	EN ISO 24340	0,7 mm	0,7 mm
Width of roll	EN ISO 24341	2/4 m	2/4 m
Length of rolls	EN ISO 24341	20 lm	20 lm
Total weight	EN ISO 23997	2,0 kg/m ²	2.6 kg/m ²
CLASSIFICATION			
European classification	EN ISO 10874	Class 34/43	Class 33/42
PERFORMANCE			
Abrasion group	MSZ EN 660-1	T	T
Residual indentation	EN ISO 24343	max 0,1 mm	max 0,2 mm
Dimensional stability	EN ISO 23999	max 0,2 %	max 0,2 %
Fire resistance	EN 13501-1	Class: Bfl-s1	Class: Bfl-s1
	Gost 30402-94	Class: G1	Class: G1
Impact sound reduction	EN ISO 140-8		DL _w (dB): 17
Slip resistance	DIN 51130	R9	R9
	EN 13893	Class: DS	Class: DS
Electrical resistance	EN 1815	< 2 kV	< 2 kV
	EN 1081	≤10 ⁹ Ω	≤10 ⁹ Ω
Chemical resistance	EN ISO 26987	✓	✓
Bacterial resistance	EN ISO 846:1999	✓	✓
Light fastness	EN 20105 B02	grade 6	grade 6
Castor chair resistance	EN ISO 4918	✓	✓
Anti-bacterial and fungicid treatment		grabosAN	grabosAN
Seaming method		heat or cold weld	heat or cold weld

PERFORMANCE FEATURES & BENEFITS

- 2/4 m widths
- Cost effective
- Dimensionally stable
- Anti bacterial
- Antistatic

RECOMMENDED USAGE

- Education • Healthcare
- Retail • Hospitality • Offices

ENVIRONMENTAL ATTRIBUTES

- Phthalate free product
- Recycled content
- No waste product
- 100% recyclable



GRABO'S RECOMMENDATION

HEALTHCARE	EDUCATION	OFFICES	HOSPITALITY
Entrance area	Entrance area	Entrance area	Entrance
Reception/Lobby	Corridors	Reception/Lobby	Reception/Lobby
Corridors	Staff rooms	Meeting/conference rooms	Restaurant/Bar
Administration offices	Conference rooms	Offices	Kitchen
Intensive care	Classrooms	Corridors	Cinema, theatre, casino
Treatment rooms	Storage rooms	Bathroom/Toilet	Corridors
Waiting rooms	Language studios	Canteen/Cafeteria	Bedrooms
Patient rooms	Libraries		Bathroom/Toilet
Laboratories	Laboratories	RETAIL	OTHER PUBLIC AREAS
Laundry	Multipurpose rooms/halls	Entrance area	Airport hall/lounge
Storage rooms	Dormitory rooms	Department stores/Sales floors	Elevators
Ramps/elevators	Dining rooms	Shops	Bus terminals
Bathroom/Toilet	Bathroom/Toilet	Food service areas	Laboratories
	Ramps/elevators	Warehouses	Small parts assembly halls

DIAMOND STANDART ■ recommended (flooring suitable for the space) ■ highly recommended (the best flooring choices for the space)
ACOUSTIC NEO ■ recommended (flooring suitable for the space) ■ highly recommended (the best flooring choices for the space)

STANDART FRESH ACOUSTIC NEO

GRABO

STANDART FRESH • ACOUSTIC NEO

CERT ISO 9001

Graboplast Floor Covering Manufacturers Ltd.
 H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-100
 www.graboplast.com

GRABO



STANDART FRESH ACOUSTIC NEO

